OregonDoor
we build the doors that build your reputation

ALSC04 *Architectural Series*

FSC® Mix 100% Structural Composite Lumber Core—HPDL

Positive Pressure	5 Ply—Architectural-Grade Laminate .050 nominal
Thickness	**Non-Rated** 1-¾" standard • 1-$^{3}/_{8}$" available upon request **Up to 20 Minute** 1-¾" only
Maximum Sizes	**Up to 20 Minute** Single 4^0 x 9^0 Pairs 8^0 x 9^0 **Non-Rated** Single 4^0 x 10^0 Pairs 8^0 x 10^0
Core & STC Rating	100% FSC® Certified Structural Composite Lumber (core contains no added formaldehyde) Door assembly may achieve a STC rating of 31 when installed with appropriate gasketing 1-¾" only (operable unit)
Edges	**Stiles:** FSC® Certified minimum width 1-¼" unless otherwise specified (1) **Rails:** FSC® Certified Structural Composite Lumber Core
Edge Construction	**Category A**: Integral intumescent edge construction available. (Not Standard)
Faces	FSC® Certified Decorative Laminate – AWI-HPDL, NEMA-LD-3 .05 nominal thickness applied over FSC® High Density Fiberboard (HDF).
Core Assembly Adhesive	**Type 1**—Waterproof Bond NAF
Face Assembly Adhesive	**Type 1**—Waterproof Bond NAF
Core Bonding	Stiles are securely bonded utilizing type 1 adhesive in conjunction with superior RF bonding technology. To ensure freedom from telegraphing of core components, the core unit is then sanded before face veneers are applied.
Warranty (2)	**Interior Use**—Life of installation **Exterior Use**—No Warranty(3)
Construction Standards	**Meet or Exceed** WDMA I.S. 1-A (meets WDMA "Extra Heavy-Duty" standards) AWI Section 1300 AWS Section 9 NFPA 80 WI Section 12 Architectural Wood Doors – Flush UBC7-2-1997 UL10C WH/ITS Labeling
Performance Standards	Meets WDMA I.S.1-A **Extra Heavy Duty** Performance. Consult factory for specific test results.
Factory Machining	> Pre-fitting >Templated hardware prep > Lite cutouts > Louver cutouts
Sustainability	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified No-Added Formaldehyde (NAF) Certified Wood, FSC® License Code FSC-C012639 Extracted: Brainerd, Minnesota. Manufactured: Winston, Oregon

(1) Edge laminate applied after face laminate. Painted edges are also available to match face laminate.
(2) See complete Oregon Door Warranty for details.
(3) Consult factory for possible 2-year exterior warranty. Additional conditions may apply.

PO Box 1960 I Winston, Oregon 97496 I t: 541.679.6791 I f: 541.679.5063 I oregondoor.com