



OregonDoor
we build the doors that build your reputation

AW6001 Architectural Series Flush Door
60-Minute Fire Rated Mineral Core



Positive Pressure		5-Ply	
Thickness	60-Minute 1-3/4" Only		
Maximum Sizes⁽¹⁾	Single 4 ^o x 9 ^o	Pairs (Standard) 8 ^o x 9 ^o	Pairs (Double Egress) 8 ^o x 8 ^o
Core	Non-combustible, asbestos free, mineral fire core		
Edges	Stiles: Per WH / ITS Testing Requirements. ⁽²⁾ Rails: Per WH / ITS Testing Requirements. ⁽³⁾		
Edge Construction	Category A: Integral intumescent edge construction available Category B: Frame mounted intumescent edge construction standard		
Faces	All commercially available species and FSC® certified ⁽⁴⁾ veneers per AWI 1300, G11; 1/50" minimum veneer thickness, medium density overlay (MDO), hardboard ⁽⁵⁾ .		
Blocking	Fire-stop blocking available for oversize rails & lock blocks as specified.		
Face Assembly Adhesive	Type 1 —Waterproof Bond		
Warranty ⁽⁶⁾	Interior Use —Life of installation	Exterior Use —No Warranty	
Construction Standards	Meet or Exceed	WDMA I.S. 1-A AWI Section 1300 WI Section 12 Architectural Wood Doors – Flush UBC7-2-1997	NFPA 80 AWS Section 9 UL10C WH/ITS Labeling Service
Performance Standards	Meets or exceeds WDMA I.S.1-A Heavy Duty Performance. Extra Heavy Duty performance can be achieved with the use of internal blocking for surface applied hardware where through bolts will not be used. Consult factory for specific test results.		
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane)		> Clear > Standard color selections
Factory Machining	> Pre-fitting > Templated hardware prep > Lite cutouts > Louver cutouts Consult factory for full list of machining options.		
Sustainability	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified Extended Producer Responsibility Program—Take Back Program LBC Compliant—Declare Label Recycled Content—Entire assembly 28% pre-consumer, 0% post-consumer Extracted: Determined by machining requirements. Manufactured: Winston, Oregon		

- (1) Contact factory for specific size requirements
- (2) Compatible hardwood edges as specified for use with stain grade face veneers. Compatible hardwood or softwood edges available for use with paint grade faces.
- (3) Wider rails and internal blocking are available for hardware reinforcement.
- (4) Entire assembly not eligible for FSC® certification even when certified veneers are selected.
- (5) Hardboard available in 3-ply construction only.
- (6) See complete Oregon Door limited door warranty for details.
- (7) Set-up fee for custom matching applies. Approval of custom samples is required prior to finishing.

