




OregonDoor
we build the doors that build your reputation

AWAF04 Architectural Series Flush Door
FSC® Mix 100% Agrifiber Core



Positive Pressure		5-Ply	
Thickness	1-3/4" Only		
Maximum Sizes	Non-Rated:	Single 4 ⁰ x 10 ⁰	Pairs 8 ⁰ x 10 ⁰
	20 minute:	Single 4 ⁰ x 9 ⁰	Pairs 8 ⁰ x 9 ⁰
	60 minute:	Single 4 ⁰ x 8 ⁰	
Core	Agrifiber composite from 100% recycled rice straw & wheat husks. Core contains no added formaldehyde. Graded to the ANSI A 208.1, Grade LD-2 specification for door core.		
Edges	Stiles:	Minimum width 1-1/4" unless otherwise specified. ^{(1) (5)} Edge banding available	
	Rails:	Minimum width 2-1/4" unless otherwise specified. ⁽²⁾	
Edge Construction	Category A: Integral intumescent edge construction available. (not standard)		
Faces	All commercially available FSC® certified veneers per AWI 1300, G11. 1/50" minimum veneer thickness, medium density overlay (MDO)		
Core Assembly Adhesive	Type 1 —Waterproof Bond		
Face Assembly Adhesive	Type 1 —Waterproof Bond		
Core Bonding	Stiles and rails are securely bonded utilizing type 1 adhesive in conjunction with superior RF bonding technology. To ensure freedom from tele-graphing of core components, the core unit is then sanded before face veneers are applied.		
Warranty ⁽³⁾	Interior Use —Life of installation	Exterior Use —No Warranty	
Construction Standards	Meet or Exceed	WDMA I.S. 1-A AWI Section 1300 WI Section 12 Architectural Wood Doors – Flush UBC7-2-1997	NFPA 80 AWS Section 9 WH/ITS Labeling Service
Performance Standards	Meets WDMA I.S.1-A Extra Heavy Duty Performance. Consult factory for specific test results.		
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear > Standard color selections > Custom color matching ⁽⁴⁾		
Factory Machining	> Pre-fitting > Templated hardware prep > Lite cutouts > Louver cutouts		
Sustainability	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified Recycled Content—Entire assembly 0% pre-consumer, 58% post-consumer. Extended Producer Responsibility Program—Take Back Program LBC Compliant—Declare Label Rapidly Renewable Material—63.3% by weight Certified Wood—Non-core components composed of FSC® Certified wood. FSC® License Code FSC-C012639 Extracted: Brainerd, Minnesota. Manufactured: Winston, Oregon		

- (1) Compatible hardwood edges as specified for use with stain grade face veneers. Compatible hardwood or softwood edges available for use with paint grade faces.
- (2) Laminated Strand Lumber (LSL) or softwood rails at factory option. Wider rail available.
- (3) See complete Oregon Door limited door warranty for details.
- (4) Set-up fee for custom matching applies. Approval of custom samples is required prior to finishing.
- (5) Standard stile construction is laminated hardwood or LSL backer with a maximum 1/4" outer matching or compatible edge. Sizing and beveling should be completed at the factory.

