OregonDoor
we build the doors that build your reputation

CSSC04 *Craftsman Series Flush Door*

FSC® Mix 100% Structural Composite Lumber Core

Positive Pressure	*5-Ply*
Thickness	1-¾" standard, 1-$^{3}/_{8}$" & 2-¼" available upon request
Maximum Sizes	**Up to 20 Minute** Single 4^0 x 9^0 Pairs 8^0 x 9^0 **Non-Rated** Single 4^0 x 10^0 Pairs 8^0 x 10^0
Core & STC Rating	100% FSC® certified structural composite lumber. Core contains no added formaldehyde. Door assembly may achieve a STC rating of 31 when installed with appropriate gasketing 1-¾" only (operable unit)
Edges	**Stiles:** FSC® Certified minimum width 1-¼" unless otherwise specified(1) **Rails:** Not applicable. Core is monolithic (4)
Edge Construction	**Category A**: Integral intumescent edge construction available. (Not Standard)
Faces	FSC® certified AA grade veneer standard in all commercially and specialty available veneers per AWI 1300, G11. • FSC® certified sketch face, DOORfx graphic, horizontal and other specialty applications available. $^{1}/_{50}$" minimum veneer thickness.
Core Assembly Adhesive	**Type 1**—waterproof bond
Face Assembly Adhesive	**Type 1**—waterproof bond
Core Bonding	Stiles are securely bonded utilizing type 1 adhesive in conjunction with superior RF bonding technology. To ensure freedom from telegraphing of core components, the core unit is then sanded before face veneers are applied.
Warranty (2)	**Interior Use**—Life of installation **Exterior Use**—No Warranty
Construction Standards	**Meet or Exceed** WDMA I.S. 1-A (meets WDMA "Extra Heavy-Duty" standards) AWI Section 1300 AWS Section 9 NFPA 80 WI Section 12 Architectural Wood Doors – Flush UBC7-2-1997 UL10C WH/ITS Labeling
Performance Standards	Meets WDMA I.S.1-A **Extra Heavy Duty** Performance. Consult factory for specific test results.
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear > Standard color selections > Custom color matching (3)
Factory Machining	> Pre-fitting >Templated hardware prep > Lite cutouts > Louver cutouts
Sustainability	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified Extended Producer Responsibility Program—Take Back Program Recycled Content—Entire assembly 17% pre-consumer, 0% post-consumer Certified Wood, FSC® License Code FSC-C012639 Extracted: Brainerd, Minnesota. Manufactured: Winston, Oregon

(1) Compatible hardwood edges as specified for use with stain grade face veneers.
(2) See complete Oregon Door limited door warranty for details.
(3) Set-up fee for custom matching applies. Approval of custom samples is required prior to finishing.
(4) SCL core does not require additional top & bottom rails.

477 Dillard Gardens Road | PO Box 1960 | Winston, Oregon 97496 | 541.679.6791 | oregondoor.com