



OregonDoor
we build the doors that build your reputation

FRP-Frame *FRP Rugged Series*
FRP Standard Frame

<i>FRP Rugged Series</i>	Fiberglass Reinforced Polymer (FRP)	
Overview	This door frame is specifically designed for use in harsh environments. Its all FRP and polymer construction is ideal for any project where the door frames are frequently exposed to water, salt, and other harsh chemicals. The frame can also be configured as four-sided and used as a window. Other options include side light frames and transoms with glass or solid panels	
Maximum Sizes	Single 4 ⁰ x 10 ⁰	Pairs 8 ⁰ x 10 ⁰
Thickness	³ / ₁₆ " Pultruded Fiberglass Reinforced Polymer (FRP)	
Style	Standard construction is knock down for field assembly. Jamb sections and head bar are secured together by an interlocking FRP angle and stainless steel screws. Frames completely assembled with chemically welded corners are also available	
Anchors	Frames are available with multiple options for anchoring to the wall. Please see Frame Anchor Option Sheet to determine the best option for your wall condition. All bolt screws, etc. needed for securing the frame to the wall are by others	
Jamb Depths	Multiple jamb depths are available	
Reinforcements	All reinforcements for locks, hinges, etc. are made from FRP	
Head Bars	2" Face Standard • 4" Available on 5- ³ / ₄ " Jamb Depths Only	
Transom Bars	2" Face made to be removable or chemically welded in place	
Finishes	Options include priming for field painting and standard or custom match finish colors. Our standard finish is an environmentally-friendly water-based product	
Warranty⁽¹⁾	Interior Use — 10 years	Exterior Use — 10 Years

1. See complete Oregon Door Limited Door Warranty for details.

