



OregonDoor
we build the doors that build your reputation

FM60 FRP Rugged Series
Smooth Face 60-Minute FRP Fire-Rated Core Door

FRP Rugged Series Fiberglass Reinforced Polymer (FRP)

Overview	This door is specifically designed for use in harsh environments. Its all FRP and polymer construction is ideal for any project where the doors are frequently exposed to water, salt, and other harsh chemicals.	
Maximum Sizes	Single 4 ⁰ x 8 ⁰	
Thickness	1-3/4" only	
Core	Non-combustible, asbestos free, NAF mineral fire core	
Stiles	Fire-Rated Composite	
Top & Bottom Rails	Fire-Rated Composite	
Blocking	Each door comes with a fire-rated composite lock block Optional blocking is available for closers and other surface-mounted hardware	
Core Assembly	Stiles and rails are securely bonded to core	
Door Faces	Standard faces are .090 thick smooth FRP Optional .120 thick smooth FRP faces are also available	
Factory Machining	>Compliant Templated Hardware Preps > Compliant Light & Louver Cutouts	
Finishes	>Primed for Field Painting >Custom Matched Paint Colors	>Standard Paint Colors
Warranty⁽¹⁾	Interior Use — 10 years	Exterior Use — 10 Years
Sustainability	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified No-Added Formaldehyde (NAF) Extracted: Canby, Oregon. Manufactured: Winston, Oregon	

(1) See complete Oregon Door FRP Rugged Series Warranty for details.

