



OregonDoor
we build the doors that build your reputation

FMSC FRP Rugged Series
Smooth Face FRP Extra Heavy Duty Core Door

FRP Rugged Series Fiberglass Reinforced Polymer (FRP)

Overview

This door is specifically designed for use in high use and abuse entrances. Its structural composite lumber (SCL) core provides structural strength and impact resistance far greater than foam core doors. The combination of core and face material provides the perfect solution for demanding applications such as schools and hospitals.

Maximum Sizes	Single 4 ⁰ x 10 ⁰	Pairs 8 ⁰ x 10 ⁰	DE Pairs 8 ⁰ x 10 ⁰
----------------------	---	--	---

Thickness	1-3/4" • 2" • 2-1/4"
------------------	----------------------

Core	Structural Composite Lumber (SCL)—38 pcf density. Core contains no added formaldehyde
-------------	---

Stiles	Solid Polymer covered with FRP Matching Door Face FRP edges applied to stiles before face
---------------	--

Top & Bottom Rails	Solid Polymer Bottom rails are oversized to allow for field trimming if necessary
-------------------------------	--

Blocking	Solid Polymer at lock location
-----------------	--------------------------------

Core Assembly	Stiles and rails are securely bonded to core
----------------------	--

Door Faces	Standard faces are .090 thick smooth FRP Optional .120 thick smooth FRP faces are also available
-------------------	---

Factory Machining	> Pre-fitting > Templated Hardware Preps > Light Cutouts > Louver Cutouts
--------------------------	--

Finishes	>Primed for Field Painting >Standard Paint Colors >Custom Matched Paint Colors
-----------------	--

Warranty⁽¹⁾	Interior Use — 10 years Exterior Use — 10 Years
-------------------------------	---

Sustainability	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified No-Added Formaldehyde (NAF) Extracted: Brainerd, Minnesota. Manufactured: Winston, Oregon
-----------------------	--

(1) See complete Oregon Door FRP Rugged Series Warranty for details.

