



**OregonDoor**  
we build the doors that build your reputation

**FMSY FRP Rugged Series**  
Smooth Face FRP Styrene Core Door

**FRP Rugged Series      Fiberglass Reinforced Polymer (FRP)**

<b>Overview</b>	This door is specifically designed for use in harsh environments. Its all FRP and polymer construction is ideal for any project where the doors are frequently exposed to water, salt, and other harsh chemicals. Its unique design is extremely strong yet lightweight.		
<b>Maximum Sizes</b>	Single 4 <sup>0</sup> x 10 <sup>0</sup>	Pairs 8 <sup>0</sup> x 10 <sup>0</sup>	DE Pairs 6 <sup>0</sup> x 7 <sup>0</sup> on 1- <sup>3</sup> / <sub>8</sub> "
<b>Thickness</b>	1- <sup>3</sup> / <sub>8</sub> " • 1- <sup>3</sup> / <sub>4</sub> " • 2" • 2- <sup>1</sup> / <sub>4</sub> "		
<b>Core</b>	2 lb. Density Closed Cell Polystyrene Foam		
<b>Stiles</b>	Solid Polymer		
<b>Top &amp; Bottom Rails</b>	Solid Polymer Bottom rails are oversized to allow for field trimming if necessary		
<b>Blocking</b>	Each door comes with polymer closer reinforcement and lock block		
<b>Core Assembly</b>	Stiles and rails are securely bonded to core		
<b>Door Faces</b>	Standard faces are .090 thick smooth FRP Optional .120 thick smooth FRP faces are also available		
<b>Factory Machining</b>	> Pre-fitting    >Templated Hardware Preps    > Light Cutouts    > Louver Cutouts		
<b>Finishes</b>	>Primed for Field Painting >Custom Matched Paint Colors		>Standard Paint Colors
<b>Warranty<sup>(1)</sup></b>	<b>Interior Use</b> — 10 years	<b>Exterior Use</b> — 10 Years	
<b>Sustainability</b>	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified No-Added Formaldehyde (NAF) Extracted: Monticello, AR. Manufactured: Winston, Oregon		

(1) See complete Oregon Door FRP Rugged Series Warranty for details.

