



OregonDoor
we build the doors that build your reputation

FPHR *FRP Rugged Series*
Pebble Face FRP Hurricane Core Door

FRP Rugged Series	Fiberglass Reinforced Polymer (FRP)	
Overview	This door is specifically designed for use in high wind areas. Its all FRP and polymer construction is not only ideal for any project where the doors are frequently exposed to water, salt, and other harsh chemicals, but is specifically designed to withstand hurricane force winds and the flying debris carried by them. The solid FRP pebble-grain faces are scratch resistant and graffiti can usually be wiped off with common cleaners.	
Maximum Sizes	Single 4 ⁰ x 7 ⁰	Pairs 8 ⁰ x 7 ⁰
Thickness	1-3/4" only	
Core	3 lb. Density Closed Cell Polystyrene Foam	
Stiles	Solid Polymer	
Top & Bottom Rails	Solid Polymer Bottom rails are oversized to allow for field trimming if necessary	
Blocking	Each door comes with polymer closer reinforcement and lock block	
Core Assembly	Stiles and rails are securely bonded to core	
Door Faces	Faces are .090 thick FRP with a pebble-grain surface and UV inhibitor	
Factory Machining	>Templated Hardware Preps approved by Florida Building Code	
Finishes	>Primed for Field Painting >Custom Matched Paint Colors	>Standard Paint Colors
Warranty⁽¹⁾	Interior Use — 10 years	Exterior Use — 10 Years
Sustainability	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified No-Added Formaldehyde (NAF) Extracted: Monticello, AR. Manufactured: Winston, Oregon	

(1) See complete Oregon Door Limited Door Warranty for details.

