



**OregonDoor**  
we build the doors that build your reputation

FPSC FRP Rugged Series  
Pebble Face FRP Extra Heavy Duty Core Door

FRP Rugged Series		Fiberglass Reinforced Polymer (FRP)	
<b>Overview</b>	This door is specifically designed for use in high use and abuse entrances. Its structural composite lumber (SCL) core provides structural strength and impact resistance far greater than foam core doors. The solid FRP pebble-grain faces are scratch resistant and graffiti can usually be wiped off with common cleaners. The combination of core and face material provides the perfect solution for demanding applications such as schools and hospitals.		
<b>Maximum Sizes</b>	Single 4 <sup>0</sup> x 10 <sup>0</sup>	Pairs 8 <sup>0</sup> x 10 <sup>0</sup>	DE Pairs 8 <sup>0</sup> x 10 <sup>0</sup>
<b>Thickness</b>	1-3/4" • 2" • 2-1/4"		
<b>Core</b>	Structural Composite Lumber (SCL)—38 pcf density. Core contains no added formaldehyde		
<b>Stiles</b>	Solid Polymer covered with FRP Matching Door Face FRP edges applied to stiles before face		
<b>Top &amp; Bottom Rails</b>	Solid Polymer Bottom rails are oversized to allow for field trimming if necessary		
<b>Blocking</b>	Solid Polymer at lock location		
<b>Core Assembly</b>	Stiles and rails are securely bonded to core		
<b>Door Faces</b>	Faces are .090 thick FRP with a pebble-grain surface and UV inhibitor		
<b>Factory Machining</b>	> Pre-fitting > Templated Hardware Preps > Light Cutouts > Louver Cutouts		
<b>Finishes</b>	>Primed for Field Painting >Custom Matched Paint Colors		>Standard Paint Colors
<b>Warranty<sup>(1)</sup></b>	<b>Interior Use</b> — 10 years		<b>Exterior Use</b> — 10 Years
<b>Sustainability</b>	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified No-Added Formaldehyde (NAF) Extracted: Brainerd, Minnesota. Manufactured: Winston, Oregon		

(1) See complete Oregon Door FRP Rugged Series Warranty for details.

