



OregonDoor
we build the doors that build your reputation

ALAF01 Architectural Series Flush Door
Agrifiber Core—HPDL

Positive Pressure		5 Ply—Architectural-Grade Laminate .050 nominal	
Thickness	1-3/4" Only		
Maximum Sizes	Non-Rated:	Single 4 ⁰ x 10 ⁰	Pairs 8 ⁰ x 10 ⁰
	20 minute:	Single 4 ⁰ x 9 ⁰	Pairs 8 ⁰ x 9 ⁰
	60 minute:	Single 4 ⁰ x 8 ⁰	
Core	Agrifiber composite from 100% recycled rice straw & wheat husks. Core contains no added formaldehyde. Graded to the ANSI A 208.1, Grade LD-2 specification for door core.		
Edges	Stiles:	Minimum width 1-1/4" unless otherwise specified. ⁽¹⁾	
	Rails:	Minimum width 2-1/4" unless otherwise specified. ⁽²⁾	
Edge Construction	Category A: Integral intumescent edge construction available. (not standard)		
Faces	Decorative Laminate – AWI-HPDL, NEMA-LD-3 .05 nominal thickness applied over High Density Fiberboard (HDF).		
Core Assembly Adhesive	Type 1 —Waterproof Bond		
Face Assembly Adhesive	Type 1 —Waterproof Bond		
Core Bonding	Stiles and rails are securely bonded utilizing type 1 adhesive in conjunction with superior RF bonding technology. To ensure freedom from tele-graphing of core components, the core unit is then sanded before face veneers are applied.		
Warranty ⁽³⁾	Interior Use —Life of installation	Exterior Use —No Warranty	
Construction Standards	Meet or Exceed	WDMA I.S. 1-A AWI Section 1300 WI Section 12 Architectural Wood Doors – Flush UBC7-2-1997	NFPA 80 AWS Section 9 WH/ITS Labeling Service
Performance Standards	Meets WDMA I.S.1-A Extra Heavy Duty Performance. Consult factory for specific test results.		
Factory Machining	> Pre-fitting > Templated hardware prep > Lite cutouts > Louver cutouts		
Sustainability	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified Extended Producer Responsibility Program—Take Back Program Recycled Content—Entire assembly 4% pre-consumer, 58% post-consumer. Rapidly Renewable Material—54.4% by weight Extracted: Brainerd, Minnesota. Manufactured: Winston, Oregon		

(1) Edge laminate applied after face laminate. Painted edges are also available to match face laminate.

(2) Laminated Strand Lumber (LSL) or softwood rails at factory option. Wider rails available upon request.

(3) See complete Oregon Door limited door warranty for details.

