



**OregonDoor**  
we build the doors that build your reputation

**AWAC4301** Architectural Series  
**Acoustic Core STC 43**



<b>Positive Pressure</b>		<b>5-Ply</b>	
<b>Thickness</b>	1-3/4" Only		
<b>Maximum Sizes</b>	<b>Non-Rated:</b> Single 4 <sup>0</sup> x 9 <sup>0</sup>	Pairs 6 <sup>0</sup> x 7 <sup>0</sup>	
	<b>Up to 20 minute:</b> Single 4 <sup>0</sup> x 8 <sup>0</sup>	Pairs not available	
<b>Core</b>	Proprietary NAF acoustic core		
<b>Edges</b>	<b>Stiles:</b> Minimum width 1-1/4" SCL with matching or compatible edge band <b>Rails:</b> Minimum width 3-5/8" SCL		
<b>Edge Construction</b>	<b>Category B:</b> Frame applied intumescent required		
<b>Faces</b>	All commercially available species veneers per AWI 1300, G11. 1/50" minimum veneer thickness, medium density overlay (MDO), hardboard <sup>(1)</sup>		
<b>Cross Bands</b>	NAF high density fiberboard (HDF)		
<b>Adhesive</b>	<b>Type 1</b> —Waterproof Bond NAF		
<b>Core Bonding</b>	Stiles and rails are securely bonded utilizing type 1 adhesive in conjunction with superior RF bonding technology. To ensure freedom from telegraphing of core components, the core unit is then sanded before face veneers are applied.		
<b>Warranty</b> <sup>(2)</sup>	<b>Interior Use</b> —Life of installation	<b>Exterior Use</b> —No Warranty	
<b>Construction Standards</b>	<b>Meet or Exceed</b> WDMA I.S. 1-A AWS Section 9 UBC7-2-1997 ASTM E 90 under Architectural Testing Inc.	NFPA 80 WH/ITS Labeling Service UL10C	
<b>Performance Standards</b>	Meets or exceeds WDMA I.S.1-A <b>Heavy Duty</b> performance		
<b>Factory Finish</b>	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane) > Clear > Standard color selections > Custom color matching <sup>(3)</sup>		
<b>Factory Machining</b>	> Pre-fitting > Templated hardware prep > Lite cutouts (consult factory) Consult factory for full list of machining options		
<b>Gasketing</b>	Gasket system #100, supplied by others, required for approved STC rating. Contact factory for hardware details and test report		
<b>Sustainability</b>	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified No-Added Formaldehyde (NAF) Extracted: Clarksville, Iowa. Manufactured: Winston, Oregon		

(1) Hardboard available in 3-ply construction only.

(2) See complete Oregon Door warranty for details.

(3) Set-up fee for custom matching applies. Approval of custom samples is required prior to finishing.

