



OregonDoor
we build the doors that build your reputation

AWHC01 Architectural Series
Hollow Core

Positive Pressure 5 Ply Hollow Core

Thickness	1- ³ / ₈ " and 1- ³ / ₄ "
Maximum Sizes	Non-Rated: Single 4 ⁰ x 10 ⁰ Pairs 8 ⁰ x 10 ⁰
Core	Honeycomb-expanded paper
Edges	Stiles: Minimum width 1- ¹ / ₄ " unless otherwise specified Rails: Minimum width 2- ¹ / ₄ " ⁽¹⁾
Edge Construction	Compatible or matching wood over SCL backer. Veneer taped edges may be used at doors taller than 9 ⁰ height.
Faces	All commercially available species veneers per AWI 1300, G11. ¹ / ₅₀ " minimum veneer thickness, medium density overlay (MDO), hardboard ⁽²⁾
Adhesive	Type 1 —Waterproof Bond NAF
Blocking	5" x 18" lock blocks and a 2- ¹ / ₄ " mid rail
Warranty ⁽³⁾	Interior Use —One Year Exterior Use —No Warranty
Construction Standards	Meet or Exceed WDMA I.S. 1-A AWI Section 1300 AWS Section 9
Performance Standards	Meets WDMA I.S.1-A Standard Duty performance
Factory Machining	> Pre-fitting > Templated hardware prep > Lite cutouts > Louver cutouts
Sustainability	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified No-Added Formaldehyde (NAF) Extracted: Medford, Oregon. Manufactured: Winston, Oregon



(1) Wider rails and internal blocking are available for hardware reinforcement.
 (2) Hardboard available in 3-ply construction only.
 (3) See complete Oregon Door Warranty for details.

