



OregonDoor
we build the doors that build your reputation

AWRC01 Architectural Series Flush Door
ReCor® Core

Positive Pressure 5-Ply

Thickness	1-3/4" standard, 1-3/8" & 2-1/4" available upon request		
Maximum Sizes	Non-Rated:	Single 4 ⁰ x 10 ⁰	Pairs 8 ⁰ x 10 ⁰
	Up to 20 Minute:	Single 4 ⁰ x 9 ⁰	Pairs 8 ⁰ x 9 ⁰
Core & STC Rating	Specialty core using post consumer recycled material extracted from an architectural wood door with a previous lifecycle. Conforms to ANSI A 208.1, minimum Grade LD-1 requirements.		
Edges	Stiles:	Minimum width 1-1/4" unless otherwise specified. ⁽¹⁾⁽⁶⁾ Edge banding available.	
	Rails:	Minimum width 2-1/4" unless otherwise specified. ⁽²⁾	
Edge Construction	Category A: Integral intumescent edge construction available. (not standard)		
Faces	All commercially available veneers per AWI 1300, G11, 1/50" minimum veneer thickness; medium density overlay (MDO), hardboard ⁽³⁾		
Core Assembly Adhesive	Type 1 —Waterproof Bond		
Face Assembly Adhesive	Type 1 —Waterproof Bond		
Core Bonding	Stiles and rails are securely bonded utilizing type 1 adhesive in conjunction with superior RF bonding technology. To ensure freedom from telegraphing of core components, the core unit is then sanded before face veneers are applied.		
Warranty⁽⁴⁾	Interior Use —Life of installation	Exterior Use —No Warranty	
Construction Standards	Meet or Exceed	WDMA I.S. 1-A	AWS Section 9
		WI Section 12 Architectural Wood Doors – Flush	
Performance Standards	Meets WDMA I.S.1-A Standard Duty Performance		
Factory Finish	WDMA TR-8/AWS System 9 (UV Cured Acrylated Polyurethane)		
	> Clear	> Standard color selections	
	> Custom color matching available ⁽⁵⁾		
Factory Machining	> Pre-fitting > Templated hardware prep > Lite cutouts > Louver cutouts Consult factory for full list of machining options		
Sustainability	CALGreen Compliant GREENGUARD and GREENGUARD Gold Certified Extended Producer Responsibility Program—Take Back Program Recycled Content—Entire assembly 11% pre-consumer, 69% post-consumer Proprietary Carbon Chain of Custody tracking Extracted: Seattle, Washington. Manufactured: Winston, Oregon		



- (1) Compatible hardwood edges as specified for use with stain grade face veneers. Compatible hardwood or softwood edges available for use with paint grade faces.
- (2) Laminated Strand Lumber (LSL) or softwood rails at factory option. Wider rail available.
- (3) Hardboard available in 3-ply construction only.
- (4) See complete Oregon Door limited door warranty for details.
- (5) Set-up fee for custom matching applies. Approval of custom samples is required prior to finishing.
- (6) Standard stile construction is laminated hardwood or LSL backer with a maximum 1/4" outer matching or compatible edge. Sizing and beveling should be completed at the factory.

