

Draft Draft Declare. SM

Architectural Series Flush Door - Fire-Rated Mineral Core w/ Wood Face Oregon Door

Final Assembly: Winston, Oregon, USA

Life Expectancy: 20 Year(s)

End of Life Options: Take Back Program

Ingredients:

Mineral Core: Perlite; Calcium sulfate (dihydrate); Portland Cement; Polyvinyl alcohol; Quartz; Glass, oxide, chemicals; **Door Skins -Veneer w/HDF Back:** Wood Dust, Soft Woods; Bleach plus Ammonia (Mixture); Slack Wax, Petroleum; **Stiles:** Perlite; Calcium sulfate (dihydrate); Portland Cement; Quartz; Wood/Wood Dust; Cellulose; **Rails:** Calcium Sulfate Dihydrate; Cellulose; Glass, oxide, chemicals; Quartz; Vermiculite; **PVA Glue:** Water; Polyvinyl acetate; Proprietary

Living Building Challenge Criteria:

I-13 Red List:

- | | |
|---|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Compliant

XXX-XXXX

EXP. 01 DEC 2021

Original Issue Date: 20XX