



OregonDoor

we build the doors that build your reputation

Agrifiber Core - FAPB-60 AWAF60

5 PLY

Thickness	1-3/4" only
Maximum Sizes	Single 4' x 8' Pairs not available
Core	Agrifiber NAUF particleboard core - 28-32# density
Stiles	Matching veneer, or HPL over Composite Fire Rated Mineral
Rails	Composite fire rated mineral, optional oversized rails available
Faces	Domestic & exotic veneers, medium density overlay, HPL or Hardboard
Crossband	High Density Fiberboard (HDF)
Core Assembly	Stiles and rails are securely bonded to core and then entire unit is sanded prior to face veneer applied
Face Adhesive	Type 1 waterproof adhesive
Performance Standards	Meets or exceeds WDMA IS.1.A21 standard duty & AWI edition 2, NAAWS 4
Fire Labeling	60 minute positive pressure Cat. B standard construction. Cat. A available. Subject to NFPA 252 and Intertek Testing Services
Factory Machining	Per hardware manufacturer's templates. Consult factory for special hardware requests.
Factory Finishing	WDMA TR-8 system 9 - UV acrylated polyurethane - clear, custom color matching, standard color selection, priming for field painting
Acoustic Rating	N/A
Warranty	Interior use - Life of Installation. Exterior use - no warranty. See complete warranty for details.
Sustainability	CALGreen Compliant, LEED v4 Credit MR sourcing and EPD, EQ low emitting material. CARB phase 2 (California Air Resources Board) compliant, TSCA Title VI, Extended Producer Responsibility Program-Take Back Program, Recycled Content & Rapidly Renewable. FSC 86% or 97% certification available when specified at time of order.

