



OregonDoor

we build the doors that build your reputation

Bullet Resistant Core AWBR Series

5 PLY

Thickness	1-3/4" only
Maximum Sizes	Single 4' x 10' Pairs 8' x 10'
Core	Bullet resistant materials levels 1,2, and 3 (per UL 752)
Stiles	Matching veneer or HPL over (SCL) or compatible hardwood stile or solid hardwood matching stile available.
Rails	Bullet resistant material
Faces	Domestic & exotic veneers, medium density overlay, HPL or 3-ply hardboard
Crossband	High Density Fiberboard (HDF)
Core Assembly	Stiles and rails are securely bonded to NAUF core and then entire unit is sanded prior to face veneer applied
Face Adhesive	Type 1 waterproof adhesive
Performance Standards	Meets or exceeds WDMA IS.1.A21 standard duty & AWI edition 2, NAAWS 4
Fire Labeling	20 minute positive pressure Cat. B standard construction. Cat. A available. Subject to NFPA 252 and Intertek Testing Services.
Factory Machining	Per hardware manufacturer's templates. Full glass lites allowed. UL 752 listed glass and metal vision kit must be factory installed. All pairs require the use of factory supplied bullet resistant metal edge and astragal. Consult factory for special hardware requests.
Factory Finishing	WDMA TR-8 system 9 - UV acrylated polyurethane - clear, custom color matching, standard color selection, priming for field painting
Acoustic Rating	N/A
Warranty	Interior use - 3 Year warranty. Exterior use - no warranty. See complete warranty for details.
Sustainability	CALGreen Compliant, LEED v4 EQ low emitting material. CARB phase 2 (California Air Resources Board) compliant, TSCA Title VI, Extended Producer Responsibility Program- Take Back Program. FSC 86% or 97% available.



477 Dillard Gardens Road | Winston, Oregon 97496 | 541.679.6791 | oregondoor.com

