

# STC Availability Chart

STC RATING	DOOR THICKNESS	FIRE RATING	OREGON GASKET #	GLASS SIZE (sq in)	GLASS TYPE	TECH DATA PAGE	PAIR OPTION	MAX SIZE
48	1 3/4	Non-Rated	<b>28</b>	–	–	<a href="#">AWAC4801</a>	–	4-0 x 8-0
48	1 3/4	20	<b>28</b>	–	–	<a href="#">AWAC4801</a>	–	4-0 x 8-0
47	1 3/4	Non-Rated	<b>28</b>	–	–	<a href="#">AWAC4701</a>	–	4-0 x 8-0
47	1 3/4	20	<b>28</b>	–	–	<a href="#">AWAC4701</a>	–	4-0 x 8-0
46	1 3/4	Non-Rated	<b>28</b>	216	5/8 laminated	<a href="#">AWAC4601</a>	–	4-0 x 8-0
46	1 3/4	20	<b>28</b>	216	7/8 Pyrostop®	<a href="#">AWAC4601</a>	–	4-0 x 8-0
46	1 3/4	45	<b>28</b>	216	7/8 Pyrostop®	<a href="#">AWAC464501</a>	–	3-0 x 7-0
45	1 3/4	Non-Rated	<b>28</b>	216	5/8 laminated	<a href="#">AWAC4501</a>	–	4-0 x 8-0
45	1 3/4	20	<b>28</b>	216	7/8 Pyrostop®	<a href="#">AWAC4501</a>	–	4-0 x 8-0
44	1 3/4	Non-Rated	<b>28</b>	216	5/8 laminated	<a href="#">AWAC4401</a>	–	4-0 x 8-0
44	1 3/4	20	<b>28</b>	216	7/8 Pyrostop®	<a href="#">AWAC4401</a>	–	4-0 x 8-0
44	1 3/4	45	<b>28</b>	484	7/8 Pyrostop®	<a href="#">AWAC444501</a>	–	3-0 x 7-0
43	1 3/4	Non-Rated	<b>28</b>	484	1/2 laminated	<a href="#">AWAC4301</a>	–	4-0 x 8-0
43	1 3/4	Non-Rated	<b>30</b>	216	5/8 laminated	<a href="#">AWAC4301</a>	Yes	8-0 x 8-0
43	1 3/4	20	<b>28</b>	484	7/8 Pyrostop®	<a href="#">AWAC4301</a>	–	4-0 x 8-0
43	1 3/4	20	<b>30</b>	216	7/8 Pyrostop®	<a href="#">AWAC4301</a>	Yes	8-0 x 8-0
43	1 3/4	45	<b>28</b>	864	7/8 Pyrostop®	<a href="#">AWAC434501</a>	–	3-0 x 7-0
41	1 3/4	Non-Rated	<b>28</b>	216	7/8 Pyrostop®	<a href="#">AWAC4101</a>	–	4-0 x 8-0
41	1 3/4	20	<b>28</b>	216	7/8 Pyrostop®	<a href="#">AWAC4101</a>	–	4-0 x 8-0
41	1 3/4	45	<b>28</b>	864	7/8 Pyrostop®	<a href="#">AWAC414501</a>	–	3-0 x 7-0
40	1 3/4	Non-Rated	<b>28</b>	864	1/2 laminated	<a href="#">AWAC4001</a>	–	4-0 x 8-0
40	1 3/4	20	<b>28</b>	864	7/8 Pyrostop®	<a href="#">AWAC4001</a>	–	4-0 x 8-0
39	1 3/4	Non-Rated	<b>30</b>	216	5/8 laminated	<a href="#">AWAC3901</a>	Yes	8-0 x 8-0
39	1 3/4	20	<b>30</b>	216	7/8 Pyrostop®	<a href="#">AWAC3901</a>	Yes	8-0 x 8-0
37	1 3/4	45-60-90	<b>32</b>	484	5/16 ceramic	<a href="#">AWAC3701</a>	–	4-0 x 8-0
36	1 3/4	Non-Rated	<b>28</b>	1296	1/4 laminated	<a href="#">AWAC3601</a>	–	4-0 x 8-0
36	1 3/4	20	<b>28</b>	484	5/16 ceramic	<a href="#">AWAC3601</a>	–	4-0 x 8-0

\*STC 46 and higher may have longer lead times

\* Factory installed glazing is required to ensure acoustic value

\* Pairs tested as standard swing only, used in double egress will affect acoustic rating and/or void fire label

\* Standard gasket set numbers shown, alternate sets with use of mortise door bottoms also available. At singles, use **29**. At pairs, use **31**. At fire rated STC37, use **33**.