STC Availability Chart

STC RATING	DOOR THICKNESS	FIRE RATING	OREGON GASKET #	GLASS SIZE (sq in)	GLASS TYPE	TECH DATA PAGE	PAIR OPTION	MAX SIZE
48	1 3/4	Non-Rated	**28**	–	–	**AWAC4801**	–	4-0 x 8-0
48	1 3/4	20	**28**	–	–	**AWAC4801**	–	4-0 x 8-0
47	1 3/4	Non-Rated	**28**	–	–	**AWAC4701**	–	4-0 x 8-0
47	1 3/4	20	**28**	–	–	**AWAC4701**	–	4-0 x 8-0
46	1 3/4	Non-Rated	**28**	216	5/8 laminated	**AWAC4601**	–	4-0 x 8-0
46	1 3/4	20	**28**	216	7/8 Pyrostop®	**AWAC4601**	–	4-0 x 8-0
46	1 3/4	45	**28**	216	7/8 Pyrostop®	**AWAC464501**	–	3-0 x 7-0
45	1 3/4	Non-Rated	**28**	216	5/8 laminated	**AWAC4501**	–	4-0 x 8-0
45	1 3/4	20	**28**	216	7/8 Pyrostop®	**AWAC4501**	–	4-0 x 8-0
44	1 3/4	Non-Rated	**28**	216	5/8 laminated	**AWAC4401**	–	4-0 x 8-0
44	1 3/4	20	**28**	216	7/8 Pyrostop®	**AWAC4401**	–	4-0 x 8-0
44	1 3/4	45	**28**	484	7/8 Pyrostop®	**AWAC444501**	–	3-0 x 7-0
43	1 3/4	Non-Rated	**28**	484	1/2 laminated	**AWAC4301**	–	4-0 x 8-0
43	1 3/4	Non-Rated	**30**	216	5/8 laminated	**AWAC4301**	Yes	8-0 x 8-0
43	1 3/4	20	**28**	484	7/8 Pyrostop®	**AWAC4301**	–	4-0 x 8-0
43	1 3/4	20	**30**	216	7/8 Pyrostop®	**AWAC4301**	Yes	8-0 x 8-0
43	1 3/4	45	**28**	864	7/8 Pyrostop®	**AWAC434501**	–	3-0 x 7-0
41	1 3/4	Non-Rated	**28**	216	7/8 Pyrostop®	**AWAC4101**	–	4-0 x 8-0
41	1 3/4	20	**28**	216	7/8 Pyrostop®	**AWAC4101**	–	4-0 x 8-0
41	1 3/4	45	**28**	864	7/8 Pyrostop®	**AWAC414501**	–	3-0 x 7-0
40	1 3/4	Non-Rated	**28**	864	1/2 laminated	**AWAC4001**	–	4-0 x 8-0
40	1 3/4	20	**28**	864	7/8 Pyrostop®	**AWAC4001**	–	4-0 x 8-0
39	1 3/4	Non-Rated	**30**	216	5/8 laminated	**AWAC3901**	Yes	8-0 x 8-0
39	1 3/4	20	**30**	216	7/8 Pyrostop®	**AWAC3901**	Yes	8-0 x 8-0
37	1 3/4	45-60-90	**32**	484	5/16 ceramic	**AWAC3701**	–	4-0 x 8-0
36	1 3/4	Non-Rated	**28**	1296	1/4 laminated	**AWAC3601**	–	4-0 x 8-0
36	1 3/4	20	**28**	484	5/16 ceramic	**AWAC3601**	–	4-0 x 8-0

*STC 46 and higher may have longer lead times

* Factory installed glazing is required to ensure acoustic value

* Pairs tested as standard swing only, used in double egress will affect acoustic rating and/or void fire label

* Standard gasket set numbers shown, alternate sets with use of mortise door bottoms also available. At singles, use **35**. At pairs, use **36**. At fire rated STC37, use **37**.